



AXIOBIB™ / XEOBIB™ R1W

**FEATURING ULTRAFLEX™ TECHNOLOGY –
A MICHELIN INNOVATION THAT ALLOWS YOU TO
CARRY THE SAME LOAD AT LOWER PRESSURES (VF),
OR HEAVIER LOADS AT THE SAME PRESSURE (IF).**

The MICHELIN® **AXIOBIB™**, the first tire in the industry consistent with the IF designation established by the U.S. Tire and Rim Association, which Michelin refers to as Increased Flexion.

NEW CLASS OF TECHNOLOGY – NEW LEVEL OF PERFORMANCE

- Ultraflex Technology creates up to a 22% larger footprint when compared to standard radials, which provides maximum ground contact, preventing soil compaction and increasing productivity.

IMPROVED SIDEWALL FLEXIBILITY

- Increased flexion offers greater sidewall flexibility without compromising endurance or service life. The MICHELIN® **AXIOBIB™** radial is the first tire in the industry consistent with the IF designation recently established by the U.S. Tire and Rim Association.

HIGH LOAD-CARRYING CAPACITY

- 20% more load capacity compared to standard tires of the same size, at the same pressure.*

A "D" SPEED RATING

- MICHELIN® **AXIOBIB™** tires are approved for road speeds of up to 40 mph.

SUPERB COMFORT

- Greater sidewall flexibility offers outstanding operator comfort, without compromising endurance or service life.

*Compared to the MICHELIN® MACHXBIB® radial.



**ASK YOUR AUTHORIZED
MICHELIN DEALER ABOUT
OUR 90 DAY SATISFACTION
GUARANTEE ON ALL
MICHELIN AG RADIALS.**



Size	I.S.O Index	Product Code	Maximum Inflation Pressure (psi)	Maximum Load 40 mph (lbs)	Section Width (in)	Overall Diameter (in)	Rolling Circumference (in)	RCI	Tread Depth (32nds)	Notes
AXIOBIB™										
IF 600/70R30 (1)	159D	96393	23	9,645	23.6	62.4	184.4	43	71	
IF 620/75R30 (1)	164D	96772	23	11,023	25.9	65.7	194.0	44	73	
IF 650/75R30 (1)	166D	96826	23	11,684	26.7	67.8	199.6	45	72	
IF 650/65R34	161D	26241	23	10,200	25.7	67.8	200.7		73	
IF 650/85R38	179D	97250	35	17,086	27.2	80.7	239.3	48	79	
IF 710/85R38	178D	99013	23	16,534	28.9	85.0	250.6	49	82	
IF 800/70R38	179D	99142	23	17,086	31.9	81.4	239.7	48	79	
IF 710/70R42	179D	99783	35	17,086	29.2	81.2	240.7	48	79	
IF 710/75R42	175D	25479	23	15,650	28.1	85.1	251.8		83	
XEOBIB™										
VF 480/60 R28 (1)	134D	80140	26	4,674	19.2	51.1	150.8	39	57	
VF 520/60 R28 (1)	138D	80236	26	5,203	21.0	52.6	155.1	40	58	
VF 600/60 R28 (1)	146D	80297	26	6,614	23.5	56.2	165.2	41	60	
VF 600/60R30 (1)	147D	03690	14	6,779	23.7	58.9	172.4	42	64	
VF 600/60 R38 (1)	151D	80626	14	7,606	23.0	66.8	197.7	44	66	
VF 650/60 R38 (1)	155D	80851	14	8,543	26.6	68.3	201.1	45	66	
VF 710/60 R38 (1)	160D	81759	14	9,921	28.0	71.4	210.8	46	68	
VF 710/60R42 (1)	161D	94391	14	10,196	28.1	75.6	223.4	47	72	

Note : Product measurements are subject to change and are listed here for your convenience. Please visit www.michelinag.com or see your Representative for the most current information.

(1) Available by special order.

Effective November 1, 2011