



CARGOXBIB®

STEEL-BELTED RADIAL

LOW PRESSURE RADIAL TIRE FOR TURF APPLICATIONS: TRAILERS, SPREADERS, TANKERS AND HARVESTERS

MICHELIN® CARGOXBIB® radial stands up to any comparison in terms of rolling resistance, load capacity and soil protection, with all the attributes of a high performance radial casing.

ULTRA LOW SOIL COMPACTION

- The MICHELIN® CARGOXBIB® carries high loads at lower pressures. With its large contact patch and rounded shoulders, the tire offers maximum flotation, minimizing rutting and soil damage.

EXCEPTIONALLY LOW ROLLING RESISTANCE

- The exceptionally low rolling resistance greatly reduces the tractive force required to pull trailers equipped with MICHELIN® CARGOXBIB® (40% less compared to bias-ply), resulting in increased productivity and fuel savings.

IMPRESSIVE LOAD CARRYING CAPACITY AT HIGH SPEED

- Radial casing and reinforced construction give extraordinary load capacity at speeds up to 40 mph.

EXCEPTIONAL STABILITY AND COMFORT

- The MICHELIN® CARGOXBIB® with its tread blocks helps improve the stability of equipment in the raised position. The tread blocks also contribute to excellent handling on sidehill slopes by providing an effective support base. Radial casing technology and low pressures provide a soft smooth ride.



ASK YOUR AUTHORIZED MICHELIN DEALER ABOUT OUR 90 DAY SATISFACTION GUARANTEE ON ALL MICHELIN AG RADIALS.

| Size | I.S.O Index | Product Code | Maximum Inflation Pressure (psi) | Maximum Load 40 mph (lbs) | Section Width (in) | Overall Diameter (in) | Rolling Circumference (in) | RCI | Tread Depth (32nds) | Notes |
|-------------------|-------------|--------------|----------------------------------|---------------------------|--------------------|-----------------------|----------------------------|-----|---------------------|-------|
| CARGOXBIB® | | | | | | | | | | |
| 500/60R22.5 | 155D | 73552 | 58 | 8,543 | 20.2 | 46.5 | 137.2 | 37 | 21 | |
| 560/60R22.5 | 161D | 75840 | 58 | 10,196 | 22.4 | 49.3 | 144.8 | 38 | 21 | |
| 600/50R22.5 | 159D | 94336 | 58 | 9,645 | 24.3 | 46.5 | 136.9 | 37 | 21 | |
| 710/45R22.5 | 165D | 49366 | 58 | 11,354 | 28.4 | 47.6 | 139.8 | | 21 | |
| 600/55R26.5 | 165D | 42913 | 58 | 11,354 | 24.6 | 53.1 | 156.5 | | 24 | |
| 710/50R26.5 | 170D | 77969 | 58 | 13,228 | 28.8 | 55.3 | 162.8 | 40 | 24 | |
| 800/45R26.5 | 174D | 81371 | 58 | 14,771 | 32.1 | 54.9 | 161.3 | 40 | 24 | |
| 600/60R30.5 | 169D | 51915 | 58 | 12,787 | 25.2 | 58.9 | 173.9 | | 26 | |
| 650/65R30.5 | 176D | 94604 | 58 | 15,653 | 26.7 | 63.9 | 188 | 43 | 29 | |
| 710/50R30.5 | 173D | 92209 | 58 | 14,330 | 28.7 | 58.9 | 173.5 | | 29 | |
| 750/60R30.5 | 181D | 83575 | 58 | 18,188 | 29.9 | 66.1 | 194.3 | | 29 | |
| 800/45R30.5 | 176D | 53255 | 58 | 15,653 | 32.3 | 58.9 | 173.5 | | 26 | |
| 850/50R30.5 | 182D | 69986 | 58 | 18,739 | 33.9 | 64.1 | 188.1 | 43 | 29 | |

| Size | I.S.O Index | Product Code | Maximum Inflation Pressure (psi) | Maximum Load 25 mph (lbs) | Section Width (in) | Overall Diameter (in) | Rolling Circumference (in) | RCI | Tread Depth (32nds) | Notes |
|--------------|-------------|--------------|----------------------------------|---------------------------|--------------------|-----------------------|----------------------------|-----|---------------------|-------|
| XP27™ | | | | | | | | | | |
| 340/65R18 | 149A8 | 08185 | 72 | 7,165 | 13.5 | 35.1 | 107.9 | 32 | 10 | |

Note : Product measurements are subject to change and are listed here for your convenience. Please visit www.michelinag.com or see your Representative for the most current information.