



MACHXBIB®

R1W

HIGH FLOTATION R1W RADIAL FOR HIGH HORSEPOWER TRACTORS

When soil protection and low compaction are critical, the huge soft footprint of the MICHELIN® MACHXBIB® rises to the challenge.

SOIL PROTECTION IS #1

- Carrying heavy loads at ultra-low pressures with a huge soft footprint and rounded shoulders, the MICHELIN® MACHXBIB® helps deliver vital soil protection during preparation, planting and treatment. Rutting is minimized.
- A flat stable tread spreads the load evenly across the footprint, helping to minimize soil compaction by providing excellent ground pressure distribution.

HIGH LOAD CAPACITY

- A large air chamber, the braced tread and the reinforced radial casing allow the MICHELIN® MACHXBIB® to carry heavy loads at low pressures.

EXTRAORDINARY TRACTION AND EFFICIENCY

- A broad flat crown with long deep lugs give the MICHELIN® MACHXBIB® a low slip rate and minimal rolling resistance, giving more traction, and resulting in time and fuel savings.

EXCEPTIONAL COMFORT AND HANDLING

- The swept-back 45° lug design delivers an exceptionally smooth ride on the road at speeds of up to 30 mph.
- An ultra-flexible but super-strong casing and low air pressures deliver sensational ride comfort in the field and on the road.



ASK YOUR AUTHORIZED MICHELIN DEALER ABOUT OUR 90 DAY SATISFACTION GUARANTEE ON ALL MICHELIN AG RADIALS.

Size	I.S.O Index	Product Code	Conversion from Std.	Maximum Inflation Pressure (psi)	Maximum Load 25 mph (lbs)	Section Width (in)	Overall Diameter (in)	Rolling Circumference (in)	RCI	Tread Depth (32nds)	Notes
MACHXBIB®											
600/65R28	154A8/154B	86350		35	8,267	24.2	58.9	174.6	42	64	
600/70R28 (2)	157A8/157B	46139		35	9,094	24.2	62.4	185.2		67	
600/70R30	152A8/152B	68024		23	7,826	23.6	63.0	186.5	43	71	
710/55R30 (2)	153A8/153B	73905		23	8,047	26.9	59.7	176.8		64	
650/75R38 (2)	169A8/169B	86829		35	12,787	26.2	76.7	226.8	47	77	
650/85R38	173A8/173B	89462		35	14,330	27.0	81.2	239.8	48	81	
710/70R38	171A8/171B	35929		35	13,558	27.9	77.0	226.1	47	76	
800/70R38	173A8/173B	72379		23	14,330	31.3	81.6	240.7	48	76	
620/70R42	166A8/166B	24383		35	11,684	25.2	76.9	228.7	47	71	
710/70R42	173A8/173B	36718		35	14,330	28.9	80.7	239.7	48	77	
900/50R42	168A8/168B	71498		23	12,346	33.6	76.7	228.9	47	72	
XM28™ LARGE VOLUME											
650/75R32 (1)	159A8/156B	77317	24.5R32	23	9,645	25.1	71.7	211.3	45	73	
680/75R32	164A8/161B	80305		23	11,023	26.6	73.4	215.6	46	73	
620/70R46	162A8/162B	69879		23	10,472	24.4	81.1	241.0	48	72	

Note : All of the above tires are tubeless but can be mounted with a tube.

Note : Product measurements are subject to change and are listed here for your convenience. Please visit www.michelinag.com or see your Representative for the most current information.

(1) Not recommended for use on Harvesters.

(2) Available by special order.