



MEGAXBIB®

STEEL-BELTED RADIAL

SUPER VOLUME HIGH FLOTATION RADIAL FOR HARVESTERS AND FLOATERS

When flotation and soil protection are needed, MICHELIN® MEGAXBIB® radials help carry heavy loads in the field with minimal risk of rutting and compaction.

ULTRA-LOW SOIL COMPACTION

- The MICHELIN® MEGAXBIB® is an excellent choice for situations where flotation and reduced compaction are critical.

IMPRESSIVE LOAD CARRYING CAPACITY

- A huge footprint and extra-large air chamber combined with a special casing design allow the MICHELIN® MEGAXBIB® to carry extremely heavy loads at relatively low pressures.

BROAD FLAT FOOTPRINT - EXCELLENT GROUND PRESSURE DISTRIBUTION

- A flat stable tread spreads the load evenly across the footprint, helping to maximize flotation and minimize soil compaction.

EXCEPTIONAL COMFORT

- Ultra-low pressures and super-flexible sidewalls give the MICHELIN® MEGAXBIB® a soft comfortable ride, with surprising stability and handling on the road.



ASK YOUR AUTHORIZED MICHELIN DEALER ABOUT OUR 90 DAY SATISFACTION GUARANTEE ON ALL MICHELIN AG RADIALS.

Size	I.S.O Index	Product Code	Equivalent Size	Maximum Inflation Pressure (psi) 6 mph Cyclic	Maximum Load 6 mph Cyclic	Section Width (in)	Overall Diameter (in)	Rolling Circumference (in)	RCI	Tread Depth (32nds)	Notes
MEGAXBIB®											
1000/50R25 (2,4)	172A8/166D	27566	66x43.00-25	41	23,610	39.6	65.0	194.2		58	
580/70R26 (XM27)	149A8/146B	49571	18.4R26	28	10,760	23.2	56.5	169.3		55	
620/70R26 (XM27)	153A8/150B	53054	16.9R30	28	12,080	24.8	59.1	175.9	42	57	
620/75R26	166A8/150B	89936	23.1-26	55	19,860	23.1	63.1	186.9	43	58	
750/65R26	166A8/166B	91020	28L-26	39	19,860	28.6	63.8	189.4		58	
750/50R26 (6)	157A8/151D	15686	54x31.00-26	41	15,450	29.9	55.3	163.9	41	48	
620/75R30 (5)	168A8/168B	63928	23.1-30	55	20,990	23.8	67.3	200.1	44	58	
650/75R32 (5)	172A8/172B	46686	24.5R-32	55	23,610	25.9	71.9	213.5	45	74	
800/65R32	172A8/172B	79035	30.5LR32	39	23,610	31.5	72.4	214.9	46	71	
900/60R32	176A8/176B	59226		39	26,610	34.0	74.6	221.0	46	71	
1050/50R32 T2 (2,4)	178A8/172D	04644	73x44.00-32	41	28,110	41.5	73.1	216.7	46	52	
1050/50R32 M28 (1,3,5)	178A8	94737	73x44.00-32	39	28,110	40.9	74.9	222.4	46	76	
620/75R34 (5)	170A8/170B	83734	23.1-34	55	22,490	23.2	71.4	212.5		58	
620/70R38 (5)	170A8/170B	99512		55	22,490	23.9	73.4	218.8	46	69	
620/70R42 (6)	166A8/166B	15145		41	17,480	25.2	76.9	228.7	47	71	

Note : All of the above tires are tubeless but can be mounted with a tube.

Note : Tires approved for Floaters must only be roaded with the machine EMPTY and at no more than 40 mph.

Note : Product measurements are subject to change and are listed here for your convenience. Please visit www.michelinag.com or see your Representative for the most current information.

(1) MICHELIN® MEGAXBIB® M28 is designed for use on harvesting machines. Deep Tread.

(2) ONLY this tire is approved for high-speed applicators like the Floaters.

(3) Not recommended for use on high-speed applicators like the Floaters.

(4) Special 40 mph speed rating.

(5) Available by special order.

(6) Available 1st Quarter 2012.