



# AGRIBIB® / AGRIBIB® ROW CROP

## RADIAL DRIVE R1W

### STANDARD PROFILE R1W DEEP LUG RADIAL FOR ALL-AROUND SERVICE

With its deep lugs, flat tread and generous footprint, this tire delivers exceptional traction in dry or wet conditions while simultaneously applying low ground pressure and helping to control soil compaction.

#### LONG TIRE LIFE

- Deep lugs, low slip and optimized rubber compounds help reduce wear to give exceptionally long tire life.
- In addition a sharp vertical lug design allows the MICHELIN® AGRIBIB® to retain traction even when 70% worn.

#### EXCEPTIONAL TRACTION: YEAR ROUND

- Strong but super-flexible sidewalls allow a long footprint, putting more lugs in direct contact with the soil.
- Michelin's exclusive "self-cleaning hinge" between the lugs ensures that the tread stays free of mud for maximum pulling power in wet conditions.

#### LOW SOIL COMPACTION - EXCELLENT FLOTATION

- A super-flat tread spreads the load evenly across a generous footprint, helping to reduce the tire's penetration into soft soil.
- Low slip and ultra-low working pressures help reduce soil compaction and damage.

#### EXCEPTIONAL COMFORT

- The swept-back 45° lug design delivers a surprisingly smooth ride on the road.
- Uniform "round" construction plus Michelin's super-strong but ultra-flexible casing deliver exceptional ride and comfort, in the field and on the road.

## AGRIBIB® ROW CROP

### REDUCED TIRE WIDTH FOR SPECIALTY APPLICATIONS

Farmers who are reducing spacing to increase yields or accommodate specialty crops such as vegetables need tires with less width, exceptional load capacity and long life.

#### REDUCED TIRE WIDTH

- The reduced width of the AGRIBIB® ROW CROP passes between valuable crops without plant and root damage.

#### REINFORCED CASING

- An extra-strong but super-flexible casing, which offers a large footprint and surprising ride comfort, has excellent durability to carry extra-heavy loads.

#### EXTRA-DEEP 40° LUGS

- Extra-deep lugs oriented at 40° provide impressive traction and excellent directional control.

#### ADDITIONAL LUGS AND STABILIZING BELTS

- Additional lugs promote slow tire wear and long service life under heavy loads at road speeds.
- Stabilizing crown belts reduce lug movement, ensuring smooth even wear.



ASK YOUR AUTHORIZED  
MICHELIN DEALER ABOUT  
OUR 90 DAY SATISFACTION  
GUARANTEE ON ALL  
MICHELIN AG RADIALS.



# AGRIBIB® / AGRIBIB® ROW CROP

## RADIAL DRIVE R1W

Size	I.S.O Index	Product Code	Equivalent Size/	Maximum Inflation Pressure (psi)	Maximum Load 25 mph (lbs)	Section Width (in)	Overall Diameter (in)	Rolling Circumference (in)	RCI	Tread Depth (32nds)	Notes
<b>AGRIBIB®</b>											
11.2R24	114A8/111B	70146		23	2,601	11.0	43.5	129.6	36	47	
12.4R24	119A8/116B	78449		23	2,988	12.8	45.2	134.6	37	52	
13.6R24	121A8/118B	97644		23	3,197	14.4	47.1	140.1	38	54	
14.9R24	126A8/123B	75971		23	3,748	16.1	49.6	147.0	39	60	
16.9R24	134A8/131B	97341		23	4,674	18.1	52.4	154.9		69	
12.4R28	121A8/118B	50465		23	3,197	12.7	49.7	148.2		50	
13.6R28	123A8/120B	87976	340/85R28	23	3,417	14.6	51.5	153.3	39	58	
14.9R28	128A8/125B	47219	380/85R28	23	3,968	15.9	53.5	159.4	40	59	
16.9R28	136A8/133B	86531	420/85R28	23	4,938	18.5	56.4	166.9	41	64	
380/85R30	135A8/135B	18784	14.9R30	23	4,806	15.2	55.7	165.1	41	58	
16.9R30 (2)	137A8/134B	41545	420/90R30	23	5,071	17.6	58.3	173.0	42	62	
420/90R30	147A8/147B	68713	16.9R30	35	6,779	17.4	60.4	179.4	42	55	
18.4R30	142A8/139B	42060		23	5,842	19.8	61.0	181.2		68	
320/85R34	133A8/130B	73532	12.4R34	35	4,541	12.7	55.7	167.1	41	49	
380/85R34	137A8/137B	59412	14.9R34	23	5,071	15.5	59.2	175.6	42	52	
420/85R34	142A8/142B	84230	16.9R34	23	5,842	17.7	62.2	184.6	43	64	
18.4R34	144A8/141B	40989		23	6,173	18.8	65.4	194.2	44	68	
12.4R38 (1)	125A8/122B	50333		23	3,638	12.2	59.1	176.6	42	44	
13.6R38	128A8/125B	66666		23	3,968	14.1	61.6	185.2	43	57	
380/80R38	142A8/142B	30231	14.9R38	35	5,842	14.9	62.1	186.1	43	58	
420/85R38	144A8/144B	84239	16.9R38	23	6,173	17.9	66	195.9	44	64	
18.4R38	146A8/143B	72676	480/80R38	23	6,614	19.3	69.6	207.0	45	68	
520/85R38	155A8/155B	43308	20.8R38	23	8,543	20.2	73.5	217.7	46	64	
480/80R42	156A8/156/B	03395	18.4R42	35	8,818	19.4	73.1	218.2	46	69	
520/85R42	157A8/157B	63687	20.8R42	23	9,094	21.2	76.6	227.2	47	74	
420/80R46	151A8/151B	58733	16.9R46	35	7,606	16.1	73.7	218.7	46	64	
480/80R46	158A8/158B	94069	18.4R46	35	9,370	18.5	76.9	231.3	47	68	
520/85R46	158A8/158B	57479	20.8R46	23	9,370	20.3	80.7	239.7	48	73	
480/80R50	159A8/159B	94576	18.4R50	35	9,645	18.7	80.9	243.5	48	68	
<b>AGRIBIB® ROW CROP SIZES</b>											
320/85R38	143A8/143B	50528	12.4R38	52	6,008	12.4	59.4	177.7	42	54	
340/85R46	150A8/150B	94547	13.6R46	52	7,385	13.3	68.8	205.8	45	52	
380/90R46	157A8/157B	38865	14.9R46	52	9,094	15.9	72.2	216.0	46	59	
320/90R50	150A8/150B	95098	12.4R50	52	7,385	12.4	72.7	221.1	46	49	
380/90R50	151A8/151B	15852	14.9R50	35	7,606	15.5	76.2	232.1	47	59	
320/90R54	151A8/151/B	96185	12.4R54	52	7,606	12.4	76.8	233.5	47	49	

Note : All of the above tires are tubeless but can be mounted with a tube.

Note : Product measurements are subject to change and are listed here for your convenience. Please visit [www.michelinag.com](http://www.michelinag.com) or see your Representative for the most current information.

(1) XM25 tread design.

(2) Not recommended to be mounted on the front axle of some MFWA tractors because of lead issues.